## Montana Board of Oil and Gas Conservation Environmental Assessment

Operator: Slawson Exploration Company, Inc.
Well Name/Number: Sentinel #1-22H
Location: NE NE Section 22 T24N R52E
County: Richland, MT; Field (or Wildcat) Wildcat
Air Quality
(possible concerns)
Long drilling time: No. 25-35 days drilling time.
Unusually deep drilling (high horsepower rig): <u>Triple derrick rig to drill a single lateral horizontal</u>
Middle Bakken Formation test, 13,008'MD/8,973'TVD.
Possible H2S gas production: Possible H2S slight.
In/near Class I air quality area: No Class I air quality area.
Air quality permit for flaring/venting (if productive): Yes, DEQ air quality permit required under 75-2-
<u>211.</u>
Mitigation:
_X Air quality permit (AQB review)
Gas plants/pipelines available for sour gas
Special equipment/procedures requirements
Other:
Comments: Triple derrick drilling rig to drill a single lateral horizontal Middle Bakken Formation
test, 13,008'MD/8,973'TVD.
Water Quality
- · · · · · · · · · · · · · · · · · · ·
(possible concerns)
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids.
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system. High water table: No high water table anticipated.
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system. High water table: No high water table anticipated. Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to
(possible concerns)  Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids.  Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.  High water table: No high water table anticipated.  Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location.
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system. High water table: No high water table anticipated. Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location. Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system. High water table: No high water table anticipated. Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location. Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'.
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system. High water table: No high water table anticipated. Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location. Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system. High water table: No high water table anticipated. Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location. Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'.
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system. High water table: No high water table anticipated. Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location. Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'. This permitted well will drill surface hole with freshwater to 1550'. Will run 1550' of steel surface casing
Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.  High water table: No high water table anticipated.  Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location.  Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'.  This permitted well will drill surface hole with freshwater to 1550'. Will run 1550' of steel surface casing and cement it to surface.  Porous/permeable soils: No, sandy clay soils.  Class I stream drainage: No, Class I stream drainages.
Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids.  Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.  High water table: No high water table anticipated.  Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location.  Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'.  This permitted well will drill surface hole with freshwater to 1550'. Will run 1550' of steel surface casing and cement it to surface.  Porous/permeable soils: No, sandy clay soils.  Class I stream drainage: No, Class I stream drainages.  Mitigation:
Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.  High water table: No high water table anticipated.  Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location.  Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'.  This permitted well will drill surface hole with freshwater to 1550'. Will run 1550' of steel surface casing and cement it to surface.  Porous/permeable soils: No, sandy clay soils.  Class I stream drainage: No, Class I stream drainages.
Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids.  Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.  High water table: No high water table anticipated.  Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location.  Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'.  This permitted well will drill surface hole with freshwater to 1550'. Will run 1550' of steel surface casing and cement it to surface.  Porous/permeable soils: No, sandy clay soils.  Class I stream drainage: No, Class I stream drainages.  Mitigation:
(possible concerns) Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids. Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.  High water table: No high water table anticipated. Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location.  Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'.  This permitted well will drill surface hole with freshwater to 1550'. Will run 1550' of steel surface casing and cement it to surface.  Porous/permeable soils: No, sandy clay soils.  Class I stream drainage: No, Class I stream drainages.  Mitigation:  X Lined reserve pit
(possible concerns)  Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids.  Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.  High water table: No high water table anticipated.  Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location.  Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'.  This permitted well will drill surface hole with freshwater to 1550'. Will run 1550' of steel surface casing and cement it to surface.  Porous/permeable soils: No, sandy clay soils.  Class I stream drainage: No, Class I stream drainages.  Mitigation:  X Lined reserve pit X Adequate surface casing
(possible concerns)  Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids.  Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.  High water table: No high water table anticipated.  Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location.  Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'. This permitted well will drill surface hole with freshwater to 1550'. Will run 1550' of steel surface casing and cement it to surface.  Porous/permeable soils: No, sandy clay soils.  Class I stream drainage: No, Class I stream drainages.  Mitigation:  X Lined reserve pit X Adequate surface casing Berms/dykes, re-routed drainage
(possible concerns)  Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids.  Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.  High water table: No high water table anticipated.  Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location.  Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'.  This permitted well will drill surface hole with freshwater to 1550'. Will run 1550' of steel surface casing and cement it to surface.  Porous/permeable soils: No, sandy clay soils.  Class I stream drainage: No, Class I stream drainages.  Mitigation:  X Lined reserve pit  X Adequate surface casing  Berms/dykes, re-routed drainage  X Closed mud system  Off-site disposal of solids/liquids (in approved facility)  Other:
(possible concerns)  Salt/oil based mud: Yes to intermediate string hole to be drilled with oil based invert drilling fluids.  Horizontal lateral will be drilled with oil based invert drilling fluids. Surface casing hole will use freshwater and freshwater mud system.  High water table: No high water table anticipated.  Surface drainage leads to live water: No, closest drainages are unnamed ephemeral tributary drainages to East Redwater Creek, about ¼ of a mile to the southwest and ¼ of a mile to the east from this location.  Water well contamination: None, closest water wells are about ¾ of a mile to the northwest and all other wells are 1 mile and further from this location. Depth of these stockwater wells range from 30' to 97'.  This permitted well will drill surface hole with freshwater to 1550'. Will run 1550' of steel surface casing and cement it to surface.  Porous/permeable soils: No, sandy clay soils.  Class I stream drainage: No, Class I stream drainages.  Mitigation:  X Lined reserve pit  X Adequate surface casing  Berms/dykes, re-routed drainage  X Closed mud system  Off-site disposal of solids/liquids (in approved facility)

1

(possible concerns)

Soils/Vegetation/Land Use

Steam crossings: None anticipated. High erosion potential: Yes, location needs a small cut, up to 7.4' and a small fill, up to 7.7', required. Loss of soil productivity: None, location to be restored after drilling well, if nonproductive. If productive unused portion of drillsite will be reclaimed.\_ Unusually large wellsite: No, large well site 400'X450' Damage to improvements: Slight, surface use is grassland. Conflict with existing land use/values: Slight Mitigation \_\_ Avoid improvements (topographic tolerance) \_\_ Exception location requested X Stockpile topsoil Stream Crossing Permit (other agency review) X Reclaim unused part of wellsite if productive \_\_\_ Special construction methods to enhance reclamation X Other: Requires DEQ General Permit for Storm Water Discharge Associated with Construction Activity, under ARM 17.30.1102(28). Comments: Access will be over existing county road, #133. Operator will construct about 408' of new access road into this location off the existing county. Oil based invert drilling fluids will be recycled. Completion fluids will be trucked to a Class II disposal. Operator will utilize a closed mud system. Cuttings and mud solids will be disposed of in the lined cuttings pit. Cuttings pit will be allowed to dry and then backfilled with subsoil clays. No concerns. Health Hazards/Noise (possible concerns) Proximity to public facilities/residences: Closest residences are more than 1 mile in any direction from this Possibility of H2S: \_Possible H2S. Size of rig/length of drilling time: Triple drilling rig 25 to 35 days drilling time. Mitigation: <u>X</u> Proper BOP equipment \_\_ Topographic sound barriers \_\_ H2S contingency and/or evacuation plan \_\_ Special equipment/procedures requirements Other: Comments: Adequate surface casing cemented to surface with a working BOP stack should mitigate any problems. Wildlife/recreation (possible concerns) Proximity to sensitive wildlife areas (DFWP identified): None identified. Proximity to recreation sites: None identified. Creation of new access to wildlife habitat: No, none. Conflict with game range/refuge management: No, none. Threatened or endangered Species: Species identified as threatened or endangered are the Pallid Sturgeon, Interior Lease Tern, Whooping Crane and Piping Plover. Candidate species are the Sprague's Pipit and the Greater Sage Grouse. NH tracker website indicates no species of concern in this area. Mitigation:

Wild Surface.
Avoidance (topographic tolerance/exception)
Other agency review (DFWP, federal agencies, DSL)
Screening/fencing of pits, drillsite
Other:

Comments: Private surface grassland, adjacent to cultivated fields. There maybe species of concern that maybe impacted by this wellsite. We ask the operator to consult with the surface owner as to what he would like done, if a species of concern are discovered at this location.

Historical/Cultural/Faleontological
(possible concerns)
Proximity to known sites: None identified
Mitigation
avoidance (topographic tolerance, location exception)
other agency review (SHPO, DSL, federal agencies)
Other:
Comments: Private surface grassland adjacent to cultivated land, There maybe possible historical/cultural/paleontological sites that maybe impacted by this wellsite. We ask the operator to consult with the surface owner as to his desires to preserve these sites or not, if they are found during construction of the wellsite.
Social/Economic
(possible concerns)
Substantial effect on tax base
Create demand for new governmental services
Population increase or relocation
Comments: No concerns.
Remarks or Special Concerns for this site  Single lateral horizontal Middle Bakken Formation test, 13,008'MD/8,973'TVD.  Summary: Evaluation of Impacts and Cumulative effects
No long term impacts expected. Some short term impacts will occur.
I conclude that the approval of the subject Notice of Intent to Drill (does/ <u>does not</u> ) constitute a major action of state government significantly affecting the quality of the human environment, and (does/ <u>does not</u> ) require the preparation of an environmental impact statement.
Prepared by (BOGC): /s/ Steven Sasaki
(title:) Chief Field Inspector
Date: October 16, 2011
Other Persons Contacted:
Bureau of Mines and Geology, GWIC website
(Name and Agency)
_Water wells in Richland County, Montana
(subject discussed)